SheerWeave® Style 7000 BLACKOUT FABRIC

Specifications

■ Style 7000 is uniquely designed to provide total light blockage when complete room darkening is needed. With a broad range of decorator colors and the look and feel of rich cloth, Style 7000 will enhance the beauty and function of any room.

Fire Classification: California U.S. Title 19 (small scale), NFPA 701-2004 TM#1 (small scale), BS 5867 2008 Part 2 Type B Performance and CAN/ULC-S109-03 (large and small scale)
Bacteria and Fungal Resistance: ASTM G21-96, AATCC 174-1998 Part II and III
Environmental Certification: GREENGUARD Certified, GREENGUARD for Children and Schools Certified, GREENGUARD Select Certified for Commercial, Healthcare and Education
Lead Free: RoHS / Directive 2002/95/EC, US Consumer Product Safety Commission Section 101 and ANSI/WCMA A100.1-2007 for lead content
Standard Use: Roll-up shade
Warranty: 5-year interior
Standard Widths: 94" and 118" (238.8cm and 299.7cm)
Standard Roll Length: 30 Linear Yards (27.4m)
Composition: 100% Polyester with Acrylic Foamed Backing **(PVC-free)**
Mesh Weight: 13.41 oz/yd^2 (454.67 g/m^2)
Fabric Thickness: .026 in (0.66mm)
Openness Factor: Opaque
Cleaning Instructions: Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to ensure compatibility.

Railroading this fabric is not recommended.
Colors may vary slightly from swatch samples. All variations are within industry standards.

Solar Heat Control Properties of Phifer SheerWeave Style 7000
Fabrics Installed Internally, Zero-Degree Profile Angle

Style No.	Color	* Solar Optical Properties TS	RS	AS	TV	Shading Coefficient w/ Single 1/8CL	1/4CL	1/4HA	Insulating 1CL	1HA
P62	White	0	64	36	0	0.31	0.31	0.30	0.30	0.24
V40	Onyx	0	64	36	0	0.31	0.31	0.30	0.30	0.24

* Performance evaluations conducted by Matrix, Inc., Mesa, Arizona.

TS = Solar Transmittance
RS = Solar Reflectance
AS = Solar Absorption
TV = Visual Transmittance

1/8 CL = 1/8" Clear Glass
1/4 CL = 1/4" Clear Glass
1/4HA = 1/4" Heat Absorbing Glass
1 CL = 1" Insulating Clear Glass
1HA = 1" Insulating Heat Absorbing Glass

For complete technical information, current test results, performance specifications and larger samples, contact our Sun Control Marketing Dept.

PHIFER INCORPORATED
P. O. BOX 1700 • TUSCALOOSA, ALABAMA 35403-1700 U.S.A.
PHONE: 205/345-2120 • TOLL FREE 1/800-221-5497
FAX: 205/391-0799 • www.phifer.com

® SheerWeave is a registered trademark of PHIFER INCORPORATED.
® GREENGUARD is a registered trademark of GREENGUARD Environmental Institute.

© PHIFER INCORPORATED
V12B 3013717